


ReForm Memory Ecotrust

Product Description



ege

THE URGE TO EXPLORE SPACE

Product description	Methods	Product data
Construction characteristics		
Structure	ISO 2424	Tufted loop pile - structured
Gauge	ISO 2424	1/12
Pile material	DIR 96/73, 96/74	100% regenerated Econyl PA6
Coloration	-	Millitron dyed
Backing	eTL	Ecotrust 350, 100% recycled
Dimensions	ISO 3018	48x48/96x96cm/Figura
Dimensional stability	EN 986	<0,2%
Total thickness	ISO 1765	Apr 8,5 mm. 0.34"
Surface pile thickness	ISO 1766	Apr 4,0 mm.
Tufts	ISO 1763	Apr 213.000 pr.m2
Total carpet weight	ISO 8543	Apr 3.050 g/m2 88.5 oz./yd2
Pile yarn weight	eTL	950 g/m2 28.03 oz./yd2
Surface pile density	ISO 8543.	Apr 0,175 g/cm3
Soil protection	eTL	Yes
Performance characteristics		
Performance areas	EN 1307	Class 33 - Commercial - Heavy
Guarantee	eTL	Contract certificate
Performance areas	Gulvbranchen	Class 33
Castor chair suitability	EN 985	Intensive use
Suitability for use on stairs	EN 1963	Yes
Static control	eTL	Permanently antistatic
Body walking test	ISO 6356	Antistatic
Acou.insu. from impact noise	ISO 717-2	25 dB
Acoustical absorption	ISO 354	0,25 aW
Suitability underfloorheating	eTL	Yes
	eTL	Apr 0,15 m2K/W
Light reflectance	eTL	Testreport
Colour fastness to light	ISO 105-B02	>5
	AATCC 16	5.0
Colour fastness to rubbing wet	ISO 105-X12	>3
	AATCC 165	5.0
Colour fastness to rubbing dry	ISO 105-X12	>3-4
	AATCC 165	5.0
Colourfast. to water patterned	ISO 105-E01	>4
Cleaning	AATCC 138	5.0
Colour fastness to ozone	AATCC 129	4.0
Colour fast.Oxides of nitrogen	AATCC 164	4.0
Other performance tests	ASTM D5252 Hexapod	4.0/ 4.5
	-	Commercial - Heavy
	AATCC 134 Electrostatic propensity	3.5 kV
Safety & Environment		
Fire classification	MK GODKENDELSE	Approved

Product description	Methods	Product data
CE Labeling	DIBT AbZ.no.	Z-156.601-441
	VKF/AEAI	Approved
	ASTM E-648	Class 1
	ASTM E662 Smoke Density	<450
	ASTM D2859 Surface Flamm.	Pass
	EN 13501-1 Euroclass	Bfl-s1
	RUSSIA	Approved
	EN 14041	Certified
	CPR	1021-CPR-010-1/16
	Declaration of Performance	DOP 5B-PA-ECT350
Indoor climate	Notified body no.	1021
	Ce Year	14
	Content of PCP EN 12673	DL
	Formaldehyde emission	NA
	Slip resistance EN 13893	Class DS
	DIM certificate	No. 006
	M1	With ECTA Backing
	BASTA	Registered
	Green Label Plus	Approved
	Emissions dans l'air intérieur	A+/A+
Environment	Environmental Choice NZ	Approved
	GECA	Approved
	BRE	ENP 434
	BREEAM-NOR	With ECTA Backing
	Environmental Product Decl.	20150334-CCA1-EN
	Cradle To Cradle Certified	Bronze certified
	Recycled Content, ISO 14021	Apr 47,0 %
	Recycled Content for LEED	Apr 39,0 %
	LEED	Qualified

Guides

Installation + adhesive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Installation tiles	Direction of installation	Quarter turn/ monolithic
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

Manufacturer characteristics

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC

ege

THE URGE TO EXPLORE SPACE

Product description	Methods	Product data
	EMAS	Audited and verified by BVC
	DS/OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified