

# Contra Stripe Broadloom

## Product Description

---



Antismudsbehandlet  
Antisoiling protected  
Schmutzabweisend  
Traitee antisalissure



Product description	Methods	Product data
<b>Construction characteristics</b>		
Structure	ISO 2424	Tufted loop pile
Gauge	ISO 2424	1/10
Pile material	DIR 96/73, 96/74	100% polyamide
Coloration	-	Continuous dyed
Backing	eTL	WT - Woven textile
Total thickness	eTL	Apr 5,5 mm.
Surface pile thickness	eTL	Apr 2,5 mm.
Total carpet weight	ISO 8543	Apr 2.125 g/m2
Pile yarn weight	eTL	700 g/m2
	.	20.65 oz./yd2
Soil protection	eTL	Yes
<b>Performance characteristics</b>		
Static control	eTL	Permanently antistatic
Suitability underfloorheating	eTL	Apr 0,09 m2K/W
Light reflectance	eTL	Testreport
<b>Safety &amp; Environment</b>		
Fire classification	EN 13501-1 Euroclass	Bfl-s1
CE Labeling	EN 14041	Certified
	CPR	1020-CPR-006-1/16
	Declaration of Performance	DOP 1B-PA-WT
	Ce Year	15
	Content of PCP EN 12673	DL
	Formaldehyde emission	NA
	Slip resistance EN 13893	Class DS
Indoor climate	Green Label Plus	Approved
<b>Guides</b>		
Installation + adhesive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
<b>Manufacturer characteristics</b>		
Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	DS/OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK

---

<b>Product description</b>	<b>Methods</b>	<b>Product data</b>
	TransQ	Qualified

---