Product description	Standard	Colortec 1100 LF	Colotec 1100 LT	Colortec 1300 LF	Colortec 1300 LT	Colotec 1500 LF	Colortec 1500 LT	Colortec 1800 LF	Colortec 1800 LT
Structure	ISO 2424	Colortec cut pile	Colortec cut pile	Colortec cut pile	Colortec cut pile	Colortec cut pile	Colortec cut pile	Colortec cut pile	Colortec cut pile
Gauge	ISO 2424	1/7"	1/7"	1/7"	1/7"	1/7"	1/7"	1/7"	1/7"
Pilematerial	-	80/20 (Wool/Nylon)	80/20 (Wool/Nylon)	80/20 (Wool/Nylon)	80/20 (Wool/Nylon)	80/20 (Wool/Nylon)	80/20 (Wool/Nylon)	80/20 (Wool/Nylon)	80/20 (Wool/Nylon)
Dyeing	-	Pre dyed	Pre dyed	Pre dyed	Pre dyed	Pre dyed	Pre dyed	Pre dyed	Pre dyed
Backing	hctl	Laminated Felt (LFB)	Laminated Textile (LTB)	Laminated Felt (LFB)	Laminated Textile (LTB)	Laminated Felt (LFB)	Laminated Textile (LTB)	Laminated Felt (LFB)	Laminated Textile (LTB)
Dimensions	ISO 3018	400 cm/500 cm	400 cm/500 cm	400 cm/500 cm	400 cm/500 cm	400 cm/500 cm	400 cm/500 cm	400 cm/500 cm	400 cm/500 cm
Pile height	ISO 1766	7,5 mm	7,5 mm	7,5 mm	7,5 mm	7,5 mm	7,5 mm	7,5 mm	7,5 mm
Total height	ISO 1765	13,5 mm	9,0 mm	13,5 mm	9,0 mm	13,5 mm	9,0 mm	13,5 mm	9,0 mm
Pile weight	ISO 8543	1100 g/m²	1100 g/m²	1300 g/m²	1300 g/m²	1500 g/m²	1500 g/m²	1800 g/m²	1800 g/m²
Total weight	ISO 8543	2020 g/m²	1700 g/m²	2200 g/m²	1880 g/m²	2370 g/m²	2060 g/m²	2640 g/m²	2330 g/m²
Tufts	ISO 1763	88320/m²	88320/m²	104328/m²	104328/m²	118400/m²	118400/m²	131376/m²	131376/m²
Colors	-	1-8 per design	1-8 per design	1-8 per design	1-8 per design	1-8 per design	1-8 per design	1-8 per design	1-8 per design
Performance areas	EN 1307	Class 32 General Contract	Class 32 General Contract	Class 32 General Contract	Class 32 General Contract	Class 33 Heavy Contract	Class 33 Heavy Contract	Class 33 Heavy Contract	Class 33 Heavy Contract
Static control	hctl	Permanent antistatic	Permanent antistatic	Permanent antistatic	Permanent antistatic	Permanent antistatic	Permanent antistatic	Permanent antistatic	Permanent antistatic
for stairs	EN 1963	No	No	Yes	Yes	Yes	Yes	Yes	Yes
for castor chairs	EN 985	No	No	No	No	No	No	No	No
Colorfastness to light	ISO 105 - B02	5 (pastel shade 4)	5 (pastel shade 4)	5 (pastel shade 4)	5 (pastel shade 4)	5 (pastel shade 4)	5 (pastel shade 4)	5 (pastel shade 4)	5 (pastel shade 4)
Colorfastness to water	ISO 105 - E01	3	3	3	3	3	3	3	3
Colorfastness wet/dry	ISO 105 - X12	3 / 4	3 / 4	3 / 4	3 / 4	3 / 4	3 / 4	3 / 4	3 / 4
Fire classification	EN 13501 - 1 IMO (USCG)	C_{fl} – S1 Certified	C_{fl} – S1 Certified	C_{fl} – S1 Certified	C_{fl} – S1 Certified	C_{fl} – S1 Certified	C_{fl} – S1 Certified	C_{fl} – S1 Certified	C_{fl} – S1 Certified
EC standard	EN 14041	Certified	Certified	Certified	Certified	Certified	Certified	Certified	Certified
Guarantee against wear	hctl	5 years	5 years	5 years	5 years	5 years	5 years	5 years	5 years

hctl = Internal test from Hammer Carpets test laboratory.
Due to ongoing development of products above declarations may change without prior notification.