

Epoca Frame

Product Description



ege

THE URGE TO EXPLORE SPACE

| Product description | Methods | Product data |
|-------------------------------------|--------------------------------|-------------------------------|
| Construction characteristics | | |
| Structure | ISO 2424 | Tufted loop pile |
| Gauge | ISO 2424 | 1/16 |
| Pile material | DIR 96/73, 96/74 | 100% polyamide |
| Coloration | - | Continuous dyed |
| Backing | eTL | WT - Woven textile |
| Dimensions | ISO 3018 | Approx. 400 cm |
| Total thickness | ISO 1765 | Apr 6,0 mm. |
| Surface pile thickness | ISO 1766 | Apr 3,0 mm. |
| Tufts | ISO 1763 | Apr 140.700 pr.m2 |
| Total carpet weight | ISO 8543 | Apr 2.300 g/m2 |
| Pile yarn weight | eTL | 850 g/m2 |
| Surface pile density | ISO 8543. | Apr 0,145 g/cm3 |
| Soil protection | eTL | Yes |
| Performance characteristics | | |
| Performance areas | EN 1307 | Class 33 - Commercial - Heavy |
| Guarantee | eTL | Contract certificate |
| Castor chair suitability | EN 985 | Intensive use |
| Suitability for use on stairs | EN 1963 | Yes |
| Static control | eTL | Permanently antistatic |
| Body walking test | ISO 6356 | Antistatic |
| Acou.insu. from impact noise | eTL | 24 dB |
| Acoustical absorption | eTL | 0,20 aW |
| Suitability underfloorheating | eTL | Apr 0,09 m2K/W |
| Light reflectance | eTL | Testreport |
| Colour fastness to light | ISO 105-B02 | >5 |
| Colour fastness to rubbing wet | ISO 105-X12 | >3 |
| Colour fastness to rubbing dry | ISO 105-X12 | >3-4 |
| Colourfast. to water patterned | ISO 105-E01 | >4 |
| Safety & Environment | | |
| Fire classification | MK GODKENDELSE | Approved |
| | EN 13501-1 Euroclass | Cfl-s1 |
| CE Labeling | EN 14041 | Certified |
| | CPR | 1021-CPR-006-2/16 |
| | Declaration of Performance | DOP 1C-PA-WT |
| | Notified body no. | 1021 |
| | Ce Year | 17 |
| | Content of PCP EN 12673 | DL |
| | Formaldehyde emission | NA |
| Indoor climate | Slip resistance EN 13893 | Class DS |
| | DIM certificate | No. 006 |
| | Green Label Plus | Approved |
| | Emissions dans l'air intérieur | A+/A+ |
| Guides | | |
| Installation + adhesive guide | DK | Dansk |
| | N | Norsk |

| Product description | Methods | Product data |
|-------------------------|---------|--------------|
| Cleaning, stain removal | S | Svensk |
| | GB | English |
| | D | Deutsch |
| | F | Francais |
| | DK | Dansk |
| | N | Norsk |
| | S | Svensk |
| | GB | English |
| | D | Deutsch |
| | F | Francais |

Manufacturer characteristics

| | | |
|-----------------------|-----------|-------------------------------|
| Factory certification | ISO 9001 | Audited and verified by BVC |
| | ISO 14001 | Audited and verified by BVC |
| | EMAS | Audited and verified by BVC |
| | DS/OHSAS | Audited and verified by BVC |
| | DS 49001 | Audited and verified by BVC |
| | CRuk | Member of Carpet Recycling UK |
| | | UK |
| | TransQ | Qualified |