

Una Micro broadloom

Product Description

Antismudsbehandlet
Antisoiling protected
Schmutzabweisend
Traitée antisalissure

contract
CERTIFICATE

egge

C11-s1

CE BASTA

A+



egge

THE URGE TO EXPLORE SPACE

Product description	Methods	Product data
Construction characteristics		
Structure	ISO 2424	Woven loop pile
Pile material	DIR 96/73, 96/74	100% solution dyed polyamide
Coloration	-	Solution dyed
Backing	eTL	WT - Woven textile
Total thickness	ISO 1765	Apr 3,0 mm. 0.12"
Total carpet weight	ISO 8543	Apr 2.400 g/m2 70.8 oz./yd2
Pile yarn weight	eTL	550 g/m2 14.16 oz./yd2
Soil protection	eTL	Yes
Performance characteristics		
Performance areas	EN15114	Class 33 - Commercial - Heavy
Guarantee	eTL	Contract certificate
Performance areas	Gulvbranchen	Class 33
Castor chair suitability	EN 985	Intensive use
Suitability for use on stairs	EN 1963	Yes
Static control	eTL	Permanently antistatic
Body walking test	ISO 6356	Antistatic
Acou.insu. from impact noise	eTL	15 dB
Acoustical absorption	eTL	0,15 aW
Suitability underfloorheating	eTL	Apr 0,05 m2K/W
Colour fastness to light	ISO 105-B02	>5
	AATCC 16	5.0
Colour fastness to rubbing wet	ISO 105-X12	>3
	AATCC 165	5.0
Colour fastness to rubbing dry	ISO 105-X12	>3-4
	AATCC 165	5.0
Colour fastness to water plain	ISO 105-E01	>3-4
Cleaning	AATCC 138	4.0
Colour fastness to ozone	AATCC 129	5.0
Colour fast.Oxides of nitrogen	AATCC 164	5.0
Other performance tests	ASTM D5252 Hexapod	4.5/5.0
	AATCC 134 Electrostatic propensity	1.3 kV
Safety & Environment		
Fire classification	MK GODKENDELSE	Approved
	DIBT AbZ.no.	Z-156.601-675
	VKF/AEAI	Approved
	ASTM E-648	Class 1
	ASTM E662 Smoke Density	<450
	ASTM D2859 Surface Flamm.	Pass
	EN 13501-1 Euroclass	Cfl-s1
CE Labeling	EN 14041	Certified
	CPR	1021-CPR-006-2/16
	Declaration of Performance	DOP 1C-PA-WT

Product description	Methods	Product data
Indoor climate	Notified body no.	1021
	Ce Year	10
	Content of PCP EN 12673	DL
	Formaldehyde emission	NA
	Slip resistance EN 13893	Class DS
	DIM certificate	No. 006
	BASTA	Registered
	Green Label Plus	Approved
	Emissions dans l'air intérieur	A+/A+
	Environmental Choice NZ	Approved
Environment	GECA	Approved
	Byggvarudeklaration	eBVD
	BREEAM-NOR	With WTA Backing
	Environmental Product Decl.	EPD-EGE-20140125-CBC1-EN
	LEED	Qualified

Guides

Installation + adhesive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

Manufacturer characteristics

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	DS/OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified